

Wall2Floor hydro-oleo repellent

Hydro-oleo repellent to restore indoor surfaces in Wall2Floor.

DESCRIPTION

Wall2Floor Sealer hydro-oleo repellent is a protective coat/sealant against water for indoors, which creates a non-film forming barrier against the passage of water and various oily substances, without considerably altering the appearance of the surface.

Wall2Floor Sealer hydro-oleo repellent is composed of a mix of fluorocarbon-based polymers and rheological additives for the restoration of indoor surfaces of the **Wall2Floor systems**.

Wall2Floor Sealer hydro-oleo repellent can be applied to restore the surface protection from dirt and scratches deriving from everyday use following wear of the protective film.

USES

Applicable on horizontal and vertical indoor surfaces, coated with **Wall2Floor system**.

Wall2Floor Sealer hydro-oleo repellent must be applied as a last coat, over at least two coats of one of the Clear Finish protective finishes (Glossy, Satin, Matt, Countertop, Countertop Ultra Matt).

IDENTIFICATION FEATURES

Binder nature: acrylic polymer in emulsion

Density:

Wall2Floor hydro-oleo repellent: 1.00 +/- 0.05 g/ml

Drying (at 25 °C and 65% R.U.): to touch in 2 hours; treadable after 24 hours.

DILUTION

Wall2Floor Sealer hydro-oleo repellent: ready to use.

WARNINGS

Mix the material adequately before laying.

Do not apply on damp substrates.

After application, the surface must not come in contact with any type of liquid for at least 24 hours. The first cleaning operations must be carried out after hardening, in general after at least **1-2 days** (calculated at an average temperature of 25°C and with 60% humidity).

Avoid highly abrasive products for cleaning and do not use steam cleaners and brushing machines.

ENVIRONMENTAL CONDITIONS

The surfaces must be protected from frost and drastic changes in temperature during the entire operating cycle. Do not apply with the temperature of the air, substrate and product under +10° C or over +35° C, or in direct sunlight or on a heated surface (even if already in the shade) or on damp or wet surfaces.

The conditions of the environment and the substrate to proceed with application of **Wall2Floor Sealer hydro-oleo repellent** are:

Environmental temperature: Min. +10 °C / Max. +35 °C

Environmental relative humidity: <75%

Substrate temperature: Min. +10 °C / Max. +35 °C

Substrate relative humidity: <4%

Application in different conditions to those described could cause deformity or defects in the chemical-physical properties and aesthetic appearance of **Wall2Floor Sealer hydro-oleo repellent**.

SUBSTRATE PREPARATION

The surface must be clean and dry, consistent and compact, dust-free and free of salt stains caused by humidity.

Consult the technical data sheet for the "**Wall2Floor System**".

APPLICATION

On the clean and dry substrate, distribute excess **Wall2Floor hydro-oleo repellent** with a wax applicator or cloth. Wait a few minutes to allow the product to penetrate the surface and remove any excess. As necessary, application is possible of a second wet on wet coat, following the previously described methods.

RECOMMENDATIONS

During all the phases to prepare the substrate, the products and application, you are advised to correctly use the equipment and personal protective equipment (PPE).

Do not expose the products for long periods to direct sources of heat or temperatures under +5°C.

If storing products at a temperature around +5°C, you are advised to bring them, before use, to a location with adequate temperature, to condition them at a use temperature not under +10°C. Don't heat the products using a direct source of heat, flame, warm body or similar.

CLEANING EQUIPMENT

With water, immediately after use.

YIELD

Wall2Floor hydro-oleo repellent: 4-8 m²/l per single coat, based on the type of substrate and its absorption rate. It is advisable to determine the real yield with a preliminary test on the specific substrate.

COLOURS

Colourless, cannot be tinted.

PACKAGING

1 l packaging.

SHELF LIFE

The product should preferably be used within 1 year of the production date if kept in the original containers unopened and in adequate temperature conditions.

The product does not require labelling pursuant to legislation in force.

Use the product according to hygiene and safety standards in force. Do not throw residue in sewers, in rivers and streams and on the ground; after use, do not dispose of the containers in the environment, leave the residue to dry well and treat as special waste. Keep out of reach of children. If ingested, consult a doctor immediately.

For further information, consult the safety data sheet.

Technical data sheet: Wall2Floor hydro-oleo repellent

Review no.: 01

Date compiled: 14-11-2018

Page 1 of 2

N.B.- COLORIFICIO NOVACOLOR guarantees the information in this data sheet is provided to the best of its experience and technical and scientific knowledge; nonetheless, the company cannot be held liable for the results obtained using these products, as application conditions are beyond its control. You are advised to always ensure the product is suited to each specific case. This data sheet voids and replaces any previously existing data sheet.

Technical data sheet: Wall2Floor hydro-oleo repellent
Review no.: 01
Date compiled: 14-11-2018
Page 2 of 2